according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

07.02.14 Article No. Issue date: (07.02.14) 1 / 10 Version Page

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

50 038 - MUSSINI medium 1 Trade name

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use

Products for creation of art.

Uses advised against

1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG Otto-Hahn-Str. 2 D - 40699 Erkrath Tel. +49 (0) 211-2509-0 Fax. +49 (0) 211-2509-497 info@schmincke.de www.schmincke.de

Dept. responsible for information

Schmincke-lab: mo-th 8.00-16.30, fr 8.00-13.30 Tel. +49 (0) 211-2509-474 Fax. +49 (0) 211-2509-11453 labor@schmincke.de

1.4 Emergency telephone number

Emergency Information

Emergencycall Berlin (24h - counseling in german and english)

+49 (0) 30 / 30 68 67 90 Phone #

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Classification according to Directive 67/548/EEC or 1999/45/EC

N dangerous for the

environment

Xn harmful

R10 Flammable.

R37 Irritating to respiratory system.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

2.2 Label elements

Labelling (CLP)

Signal word

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

07.02.14 Article No. Issue date: (07.02.14) 2 / Version Page

Hazard statements

Safety precautions

Labelling (67/548/EEC or 1999/45)

Nature of Hazard

N dangerous for the environment Xn harmful





R phrase(s)

R10 Flammable.

R37 Irritating to respiratory system.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

S phrase(s)

S2 Keep out of the reach of children.

S23 Do not breathe vapours.

S24 Avoid contact with skin.

S61 Avoid release to the environment. Refer to special instructions/safety data sheet.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

2.3 Other hazards

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterization

white spirit aldehyde resin natural oils

> **CAS-Number** EINECS / ELINCS / NLP EU index number Customs tariff number REACH registration No. RTECS-no. Hazchem-Code CI-Number

3.2 Mixtures

Substance 1

Naphtha (petroleum), hydrodesulfurized heavy: 25 - 50 %

CAS-Number: 64742-82-1

Substance 2

Light solvent naphtha: 25 - 50 %

CAS-Number: 64742-95-6

REACH registration No.: 01-2119455851-35

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

 Article No.
 Issue date:
 07.02.14

 Version
 5 (07.02.14)
 Page
 3 / 10

Classification according to Directive 67/548/EEC or 1999/45/EC:

Nature of Hazard: N - Xn / R phrase(s): 10 - 51/53 - 65

- 66 - 67

Classification according to EC regulation 1272/2008 (CLP): Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / EUH066 / Flam. Liq. 3; H226 / STOT SE 3; H336

Classification according to Directive 67/548/EEC or 1999/45/EC:

Nature of Hazard: N - Xn / R phrase(s): 10 - 37 - 51/53 - 65 - 66 - 67

Classification according to EC regulation 1272/2008 (CLP): Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3; H336

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

In case of inhalation

Provide fresh air. Seek medical attention if problems persist.

In case of skin contact

Remove residues with soap and water. In case of skin irritation, consult a physician.

After eye contact

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 10 - 15 minutes. Seek medical attention if irritation persists.

After swallowing

Rinse mouth with water. Do NOT induce vomiting. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

--

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

6.2 environmental precautions

Discharge into the environment must be avoided.

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

07.02.14 Article No. Issue date: (07.02.14) 4 / Version 10 **Page**

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose.

Additional information

6.4 Reference to other sections

Dispose of waste according to applicable legislation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Precautions against fire and explosion

No special measures are required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Hints on joint storage

Storage class

Further details

Protect from frost and exposure to sun.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Naphtha (petroleum), hydrodesulfurized heavy

DEU WEL	300,000	mg/kg	-
Light solvent naphtha			
DEU WEL	100,000	mg/m³	TRGS 900

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Hand protection

Protective gloves

Qualified materials: Nitrile rubber

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection

Goggles

Body protection

Wear suitable protective clothing.

General protection and hygiene measures
Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

 Article No.
 Issue date:
 07.02.14

 Version
 5 (07.02.14)
 Page
 5 / 10

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

Physical state liquid
Colour yellowish, clear
Odour white spirit

	min	max	
Boiling temperature/boiling			
range			
Melting point/melting range			
Flash point/flash point range	40 °C	40 °C	
Flammability			
Ignition temperature			
Autoflammability			
Explosion limits			
Refraction index			
Partition coefficient n-octanol/water			
Partition coefficient n-octanol/water			
Partition coefficient n-octanol/water Explosive properties			
·			
·			
Explosive properties	 0,8 g/ml		
Explosive properties Vapour pressure			
Explosive properties Vapour pressure Density	0,8 g/ml	 20 °C	
Explosive properties Vapour pressure Density	0,8 g/ml	 20 °C	

9.2 Other information

Viscosity dynamic up to

Viscosity kinematic of

Viscosity kinematic up to

__

SECTION 10: Stability and reactivity

40 °C

40 °C

1 mm²/s

 $3 \text{ mm}^2/\text{s}$

10.1 Reactivity

Product is stable under normal storage conditions.

10.2 Chemical stability

10.3 Possibility of hazardous reactions

--

10.4 Conditions to avoid

Protect from frost and exposure to sun.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

In case of inhalation

No data available

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

 Article No.
 Issue date:
 07.02.14

 Version
 5 (07.02.14)
 Page
 6 / 10

After swallowing

No data available

In case of skin contact

No data available

After eye contact

No data available

Practical experience

General remarks

Toxicological tests

oral	not required	Rat	>	2000,000	Maximum dose (mg/kg):	-	
Naphtha (petroleum), hydrodesulfurized heavy							
oral	LD50	Rat		2000,000	mg/kg	-	
dermal	LD50	Rat		2000,000	mg/kg	-	
Light solvent naphtha							
oral	LD50	Rat		2000,000	mg/kg	-	
dermal	LD50	Rat		2000,000	mg/kg	-	

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

No data available

Water Hazard Class 2
WGK catalog number ---

General information

12.2 Persistence and degradability

Further details

Product is partially biodegradable.

Oxygen demand

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)

Partition coefficient n-octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

--

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

 Article No.
 Issue date:
 07.02.14

 Version
 5 (07.02.14)
 Page
 7 / 10

Ecotoxicological effects

Naphtha (petroleum), hydrodesulfurized heavy

LC50	fish	10,000	mg/L	-
EC50	Algae	10,000	mg/L	-

Light solvent naphtha

LC50	fish	10,000	mg/L	-
LC50	Algae	10,000	mg/L	-

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number

080111* waste paint and varnish containing organic solvents or other dangerous substances

Recommendation

Contaminated packaging

Waste key number

--- --

Recommendation

Additional information

SECTION 14: Transport information

14.1 UN number

1263

14.2 UN proper shipping name

ADR, ADN Paint related material PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR, ADN 3 **IMDG** 3 **IATA** 3

14.4 Packing group

TTT

14.5 Environmental hazards

Marine Pollutant - IMDG Yes
Marine Pollutant - ADN Yes

14.6 Special precautions for user

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

Article No.		Issue date:	07.02.14
Version	5 (07.02.14)	Page	8 / 10

Land transport

Code: ADR/RID F1 Hazard label ADR **Limited quantities** 5L

P001 - IBC03 - LP01 - R001 **Contaminated packaging: Instructions**

PP1 **Contaminated packaging: Special provisions** MP19 Special provisions for packing together T2 **Portable tanks: Instructions** TP1 - TP29 Portable tanks: Special provisions **LGBF** Tank coding D/E **Tunnel restriction** Remarks E1

163 - 640E - 650 **Special provisions**

Inland waterway craft

EQ

Hazard label Limited quantities Transport permitted Equipment necessary Ventilation Remarks EQ **Special provisions**

Sea transport

F-E, S-E **Special provisions** 163 - 223 - 955 **Limited quantities** P001 - LP01 **Contaminated packaging: Instructions** PP1 **Contaminated packaging: Special provisions IBC: Instructions** IBC03 **IBC: Provisions Tank instructions IMO** T2 **Tank instructions UN** TP1 - TP29 **Tank instructions Special provisions** category A Stowage and segregation **Properties and observations** Remarks

Air transport

ΕQ

Flammable Liquid Hazard 309 (60L) **Passenger** Y309 (10L) Passenger LQ 310 (220L) Cargo 3L **ERG** Remarks EQ

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

Special Provisioning

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

E1

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

Article No.		Issue date:	07.02.14
Version	5 (07.02.14)	Page	9 / 10
<u>Europe</u>			
Contents of VOC [%]			
Contents of VOC			
[g/L] Further regulations, limitati	ons and legal requirements		
<u>Germany</u>			
Storage class			
Water Hazard Class	2		
WGK catalog number			

<u>Denmark</u>

Incident regulation

Information on working limitations

Further regulations, limitations and legal requirements

Further regulations, limitations and legal requirements

Hungary

 $\label{lem:continuous} \textbf{Further regulations, limitations and legal requirements}$

Great Britain

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%] 90 - 95 %

Further regulations, limitations and legal requirements

<u>USA</u>

Further regulations, limitations and legal requirements

---Federal Regulations

State Regulations

<u>Japan</u>

Further regulations, limitations and legal requirements

--

Canada

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

--

SECTION 16: Other information

Further information

R phrase(s)

R10 Flammable.

according to Regulation (EC) No. 1907/2006 (REACH)

50 038 - MUSSINI medium 1

07.02.14

Article No.		Issue date:	07.			
Version	5 (07.02.14)	Page	10 /			
	R37 Irritating to respiratory system.					
	R51/53 Toxic to aquatic organisms, may environment.	cause long-term adverse effects in the aquati	С			
	R65 Harmful: may cause lung damage if	swallowed.				
	R66 Repeated exposure may cause skin	dryness or cracking.				
	R67 Vapours may cause drowsiness and	dizziness.				
Hazard statements (CLP)	H226 Flammable liquid and vapour.					
	H304 May be fatal if swallowed and enters airways.					
	H335 May cause respiratory irritation.					
	H336 May cause drowsiness or dizziness.					

Further information

This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Literature

Reason of change

--

Additional information
