

SAFETY DATA SHEET

PICTURE VARNISH GLOSS / MATT

PRODUCT NAME: PICTURE VARNISH GLOSS / MATT

DATE OF COMPILATION: 16/07/2008

REVISION DATE: 30/09/2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: PICTURE VARNISH GLOSS/MATT

1.2 Details of the supplier of the safety data sheet: Jackson's Art Supplies

1 Farleigh Place N16 7SX London www.jacksonsart.com

Telf: +44 (0)207 254 0077

9-5:30 Mon-Fri 10-6 Saturday

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226

Most important adverse effects: Flammable liquid and vapour.

2.2. Label elements

Hazard statements: H226: Flammable liquid and vapour.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS09: Environmental





Precautionary statements:

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P234: Keep only in original container.

P264: Wash hands thoroughly after handling.

P281: Use personal protective equipment as required.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.2. Other Hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Hazardous ingredients:

2-METHOXY-1-METHYLETHYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	50-70%

1-METHOXY-2-PROPANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-539-1	107-98-2	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336	1-10%

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Consult a doctor in case of discomfort with this Security Data Sheet.

By inhalation:

Consult a doctor.

By skin contact:

Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

By eye contact:

Bathe the eye with running water for 15 minutes.

By ingestion:

Wash out mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact:

There may be mild irritation at the site of contact.

Eye contact:

There may be irritation and redness.

Ingestion:

There may be irritation of the throat.

Inhalation:

No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2 Special hazards arising from the substance or mixture

Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3 Advice for fire-fighters

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.. Personal precautions, protective equipment and emergency procedures

Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2 Environmental precautions

Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3 Methods and material for containment and cleaning up

Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4 Reference to other sections

Refer to section 8 of SDS.

SECTION 7: HANDLING AND STORAGE

7.1 Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.2 Specific end use(s)

Specific end use(s): No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Workplace exposure limits

Respirable Dust

STATE	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	100	125	-	-

Hazardous ingredients:

2-METHOXY-1-METHYLETHYL ACETATE

Workplace exposure limits Respirable Dust

UK 274 mg/m3 548 mg/m3 - -

1-METHOXY-2-PROPANOL

UK 375 mg/m3 560 mg/m3 - -

DNEL / PNEC: No data available.

8.2 Exposure controls

Respiratory protection: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

State: Liquid Colour: Colourless Odour: Aromatic

Solubility in water: Insoluble Viscosity: Non-viscous Boiling point/range°C: 180-220

Flash point°C: 42 Autoflammability°C: 200> Relative density: 1.09

9.2 Other information

No data available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Stable under recommended transport or storage conditions.

Chemical stability: Stable under normal conditions. Stable at room temperature.

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Hazardous decomposition products: In combustion emits toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Hazardous ingredients:

2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure:

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity values: No data available.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Mobility: Readily absorbed into soil.

PBT identification: This product is not identified as a PBT/vPvB substance.

Other adverse effects: Negligible ecotoxicity.

SECTION 13: DISPOSAL

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number: UN1263

14.2. UN proper shipping name Shipping name: PAINT

14.3. Transport hazard class(es): 3

14.4. Packing group: III

14.5. Environmental hazards:

Environmentally hazardous: NO

14.6. Special precautions for user:

Special precautions: No special precautions.

Tunnel code: D/E Transport category: 3

SECTION 15: REGULATORY INFORMATION

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: ADDITIONAL INFORMATION

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3:

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.