

50 032 bronze medium

product name:

- Bronze medium.

contains:

- Cumarone resin, mineral spirit.

basic information:

- Ready-to-use binder for Schmincke *oil-bronzes* (in former times *wet bronze powders*). For brilliant iridescent metallic effects on oil paintings and several other pre-primed surfaces like wood, metal or gypsum.

characteristics:

- Dries wipe and water-resistant
- remains soluble to oil of turpentine or turpentine substitute after drying.

handling:

- Shake well before use.
- Mix 3 parts Schmincke *oil-bronze* and 2 parts *bronze medium* with a painting knife shortly before application.
- The product is ready to use. The mixture can be diluted with e.g. *turpentine substitute 50019*.
- Dries wipe and water-resistant. Colour layer remains soluble to *oil of turpentine 50024 / 50102* and *turpentine substitute 50019* after getting dry.
- Please clean tools like brushes or palettes as soon as possible with e.g. *oil of turpentine 50024 / 50102*, *turpentine substitute 50019* or *brush cleaner 50051 / 50052*.
- When used on absorbent surfaces, we recommend an additional pre-treatment with *bronze medium* thinned with *turpentine substitute 50019*.
- Can be varnished carefully when dried completely with *Universal varnish AEROSPRAY glossy 50590* (oil paintings should dry at least 8 – 12 months before varnishing; pre-tests are required cause the painting layer remains soluble in *oil of turpentine / turpentine substitute*.)
- Only suitable for indoor objects (not for damp rooms!).
- Close immediately after use.
- Store in a cool and dry place.
- Individual pre-tests are required (see footer).

product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de.

DrK/ 01.02.2015/V2

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.